TROLLEYS MAY 2023 Proud of my equipment 15

TROLLEYS



SERVING TROLLEYS

Safe transport: press-drawn trays 10 mm deep for optimum holding of containers.

TOURNUS **ASSETS**

- Comfort: sound-proofed trays.
- Sturdiness: welded assembly over the whole tray height with flattened edges in lower part.

PLATE TROLLEY Raised platform

Sturdiness: bent square (25 \times 25) tube and bent sheet metal with flattened edges. Stainless steel structure.

• Ergonomical: platform height: 460 mm (200 plates) and 485 mm (400 plates).



HEATED TROLLEYS

Easy use:

no tools required to adjust plate diameter (up to 320 mm).

- Quality of steering: silent, easy sliding, reliability
- Easy cleaning: removable heated sections for deep cleaning. Flexible plug and lead with parking socket

GN RACKING TROLLEYS

- Strength: load 250 kg per trolley.
- Sturdiness: continuous welded sliders over the whole height.
- Optimum accessibility longitudinal reinforcement bar not necessary at the front.
- Swivel wheels Ø 125 mm with non-marking tyre, soundless.





Flash on our documentation!









SERVING TROLLEYS





Stainless steel welded construction. Stainless steel trays with rounded edges, soundproofed trays. Arched handles: tube Ø 25 mm. 4 swivel wheels Ø 125 mm with polyamide cover including 2 brakes, with annular bumpers. Non-marking rubber tyres. Max load: 50 kg by level. Hygiene certified.

Serving trolleys with 2 arched handles

Serving trolleys with 2 arched handles	Overall Dim. $I \times W \times h \text{ (mm)}$	Space between trays	Ref.	Price
2 trays 800 \times 530 mm	895 × 625 × 960	560	801 542	
3 trays 800 \times 530 mm	895 × 625 × 960	260	801 543	
4 trays 800 × 530 mm	895 × 625 × 1260	260	801 544	
2 trays 1000 \times 600 mm	1095 × 695 × 960	560	801 552	
3 trays 1000 × 600 mm	1095 × 695 × 960	260	801 553	
4 trays 1000 × 600 mm	1095 × 695 × 1260	260	801 554	



- Press-drawn trays with peripheral surround of 10 mm.
- Shelf width of 530 mm for efficient holding of a GN container and optimum safety of use.

Serving trolleys with 1 arched handle

	•			
Serving trolleys with 1 arched handle	Overall Dim. $I \times W \times h \text{ (mm)}$	Space between trays	Ref.	Price
2 trays 800 × 530 mm	895 × 625 × 960	560	801 602	
3 trays 800 \times 530 mm	895 × 625 × 960	260	801 603	
2 trays 1000 × 600 mm	1095 × 695 × 960	560	801 612	
3 trays 1000 × 600 mm	1095 × 695 × 960	260	801 613	



















Serving trolleys with 2 arched handles and gallery rails

Gallery rails height 50 mm in stainless steel wire Ø 8 mm, around all 4 sides for each

Serving trolleys with 2 arched handles	Overall Dim. $I \times W \times h \text{ (mm)}$	Space between trays	Ref.	Price
2 trays $800 \times 530 \text{ mm}$ with gallery rails	895 × 625 × 960	560	801 546	
3 trays 800 \times 530 mm with gallery rails	895 × 625 × 960	260	801 547	
2 trays 1000 \times 600 mm with gallery rails	1095 × 695 × 960	560	801 556	
3 trays 1000 \times 600 mm with gallery rails	1095 × 695 × 960	260	801 557	



Serving trolley delivered as flat pack item

Clearing trolleys with 2 arched handles, delivered as flat pack item. Tray assembly by screw on tubes to a pre-adjusted height.

Serving trolley (flat pack)	Overall Dim. I × W × h (mm)	Space between trays	Reference	Price
2 trays 800 × 530 mm	895 × 625 × 960	560	801 572	
3 trays 800 \times 530 mm	895 × 625 × 960	260	801 573	
2 trays 1000 × 600 mm	1095 × 695 × 960	560	801 582	
3 trays 1000 × 600 mm	1095 × 695 × 960	260	801 583	

801 395 801 538



801 537



Accessories

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Hook-on cutlery pan 1/3 GN	325 × 176 × 200	801 395	
Hook-on waste pan	420 × 200 × 250	<u>801 537</u>	
Hook-on dustbin bag support 70 litres	360 × 355 × 810	801 538	
Trolley covers 895 \times 625 mm		229 603	
Trolley covers 1095 \times 695 mm		229 604	



Option

Extra cost for serving trolleys with stainless steel wheels (83 instead of 80)









CONSTANT LEVEL PLATE DISPENSERS



Stainless steel construction. Rounded inside angles for easy cleaning. Stainless steel steering handle, stainless steel tube \emptyset 25 mm.

4 moulded polyethylene protective bumpers. 4 swivel wheels \varnothing 125 mm with polyamide cover including 2 brakes. Removable constant level dispensers, stack height 580 mm, approximately 60 plates \varnothing 180 to 290 mm.

Mobile heated plate dispensers

Powered by on/off switch with lamp. Static heating controlled by mechanical thermostat adjustable from 0°C to 90°C .

Heated by 2 stainless steel shielded elements located on the sides. Rock wool insulation. Power rating 800 W (1 stack) and 1500 W (2 stacks), voltage 230 V. Trolleys delivered with transparent polycarbonate lids.

Heated plate trolleys	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Heated single plate stack type with lid	530 × 485 × 900	808 171	
Heated twin plate stack type with lids	960 × 485 × 900	808 172	
Heated twin plate stack type with lids (for plate diam. 215-320 mm)	990 × 520 × 900	808 177	



Mobile ambient plate dispensers

Option: lids.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Ambient single plate stack type without lid.	530 × 485 × 900	808 181	
Ambient twin plate stack type without lids.	960 × 485 × 900	808 182	



- Plate holding trays guided by easy sliding, noiseless rollers.
- Handling level easily adjusted by adding or removing springs without using tools.
- **Protection:** bumpers made of non-marking composite material in the 4 corners.

Mobile universal plate dispensers

Trolleys with rectangular platform for all types of dishes (bowls, saucers, oval or rectangular plates). Heated unit c/w stainless steel lid. Ambient unit is not supplied with lid but is optional.

Description	Overall Dim. I × W × h (mm)	Reference	Price
Ambient universal trolley (open top)	960 × 485 × 900	808 201	
Heated universal trolley (with lid)	960 × 485 × 900	808 205	



Accessories

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Transparent polycarbonate lid	Ø 375	230 079	
Stainless steel lid for ambient universal trolley	750 × 415	119 268	
















GLASSES OR TRAY DISPENSER TROLLEYS



(pans GN1/3 not supplied)



Description	Overall Dim. I × W × h (mm)	Reference	Price
Self-levelling glass dispenser trolley capacity: 6 baskets 510 \times 510 mm, height 115 mm or 10 baskets, height 75 mm	817 × 545 × 930	808 102	
Self-levelling glass dispenser trolley with draining pan (GN1/2 polyethylene, depth. 100 mm) under platform 510 × 510 mm with diamond point base, capacity: 6 baskets, height 115 mm or 10 baskets, height 75 mm.	817 × 545 × 930	808 100	
Self-levelling tray dispenser trolley stainless steel surround cover capacity: 6 baskets 530 \times 530 mm, height 115 mm or 10 baskets, height 75 mm	835 × 645 × 1040	808 103	
Self-levelling tray dispenser trolley platform 540 \times 380 mm, capacity: 140 trays	817 × 545 × 930	<u>808 105</u>	
Self-levelling tray dispenser trolley stainless steel surround and cover capacity: 140 trays 560 $ imes$ 400 mm	705 × 675 × 1040	808 108	
Self-levelling tray dispenser trolley with lateral guide, capacity: 140 trays $540 \times 380 \text{ mm}$	817 × 545 × 930	808 106	
Self-levelling trolley for ABS plastic tray capacity: 140 trays $610 \times 410 \text{ mm}$	860 × 545 × 930	808 109	

Options for trolleys

Description	Reference	Price
Cutlery dispenser fitted on tray dispenser trolleys	808 107	
Polyamide cover 870 \times 540 \times 800 mm for glasses or tray dispenser trolleys	221 233	
Polyamide cover 920 \times 570 \times 1070 mm for cutlery dispenser trolleys	221 232	



Extra-cost for 4 stainless steel wheels in lieu of polyamide type wheel (plates, glasses and trays) (83 instead of 80)

Drop in dispensers with removable insert

Drop in dispenser capacities: ambient or heated plate dispenser: up to 60 plates, 180-290 mm diameter. Glasses dispenser, 6 baskets height 115 mm or 10 baskets height 75 mm. Tray dispenser: up to 140 trays. Heated dispenser provided with lid & remote control mounting switch.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Ambient single plate stack drop in dispenser without lid	Ø 380 × h. 740	<u>808 231</u>	
Heated single plate stack drop in dispenser with lid	Ø 380 × h. 740	<u>808 235</u>	
Drop in glasses dispenser	690 × 710 × 715	808 236	
Drop in tray dispenser (for up to 460 \times 360 mm tray).	580 × 660 × 715	808 237	











SELF-SERVICE TROLLEYS

Stainless steel construction. Frame in 25×25 mm stainless steel tube. Longitudinal reinforcing bars in 50×25 mm stainless steel tube. Wire type tray runner panels in 4.8mm diameter s/steel, welded to frame. With or without beige laminate side modesty panels thickness 2 mm fixed by clips. 4 swivel wheels Ø 125 m with polyamide cover including 2 braked. Annular bumpers.



6 tier (tray entry width ways)

Trolley with entry side by side. Capacity: 12 or 18 trays depending on the models. Space between tiers: 125 mm.

Description	Overall dim. $L \times w \times h$ (mm)	Width of trays	Trolleys without panels		Trolley beige	
		(mm)	Ref.	Price	Ref.	Price
Trolley 2 \times 6 tiers	930 × 630 × 1030	320 à 370	800 071		800 072	
Trolley 2×6 tiers with upper shelf	930 × 630 × 1040	320 à 370	800 073		800 074	
Trolley 3×6 tiers with upper shelf	1340 × 630 × 1040	320 à 370	800 075		800 076	



12 tier (tray entry width ways)

`		,				
Description	Overall Dim. I × W × h (mm)	Width of trays (mm)	trolleys without panels			leys ge panels
		(11111)	Ref.	Price	Ref.	Price
Trolley 1 × 12 tiers	510 × 630 × 1790	320 to 370	800 081		800 082	
Trolley 2 × 12 tiers	930 × 630 × 1790	320 to 370	800 091		800 092	



12 tier (tray entry length ways)

Capacity: 24 trays, entry back to back. Space between tiers: 125 mm.

Description	Overall dim. L × w × h	Length oftrays	Troll without	•	Trol with p	-
	(mm)	(mm)	Ref.	Price	Ref.	Price
Trolley 2 × 12 tiers	620 × 790 × 1790	400 à 480	800 093		800 094	
Trolley 2 × 12 tiers	700 × 790 × 1790	480 à 560	800 095		800 096	

Option

Extra cost for self-service trolleys with 4 stainless steel wheels (83 instead of 80)











Choose the colors of your cladding

The standard side modesty panels of the self-service trolleys are made of 2 mm thick compact beige laminate

You can personalise the cladding of the 2 outsides of your trolleys in one of the colours below (minimum order of 3 trolleys):

- Ref. 702 097, personalised cladding for trolley with 6 tiers / EXTRA CHARGE PER TROLLEY
- Ref. 702 098, personalised cladding for trolley with 12 tiers with insertion widthways / EXTRA CHARGE PER TROLLEY
- Ref. 702 099, personalised cladding for trolley with 12 tiers with insertion lengthways / EXTRA CHARGE PER TROLLEY

Personalisation is done by bonding a resistive film (cleaning resistant) to the top side of the laminated surfaces. We offer a choice of 19 colours covering cladding (swatch on request).

STANDARD COLOURS TO MATCH THE CLADDING OF TOURNUS DISPENSING UNITS

Delft Blue	Chilli Red	Brilliant Yellow	Citrus Yellow	Lime Green	Orange	Fuchsia Pink
Crocus pink	Black	Light Concrete	Dark Grey Chicago Concrete	Brushed Aluminium	Alpine White	
Champagne Hard Maple	Natural Bardolino Oak	Oiled Kendal Oak	Shorewood	Lava Grey Fleetwood	Tobacco Pacific Walnut	

Trolleys can also be personalised with your logo or that of your customers: please make enquiries with us.

TROLLEY FOR DISHWASHER BASKETS



Trolley with 8 tiers for horizontal storage of dishwasher baskets. Stainless steel construction. Square tubular leg 25×25 mm.Continuous argon welded basket runners. 4 swivel wheels 125 mm, 2 brakes, with polyamide cover. Annular wheel guards. Space between tiers: 189 mm.

Trolley (for storage of dishwasher baskets on end): welded stainless steel construction. 25 \times 25 mm tubular structure, 3 tiers with a spacing of 535 mm, including a handrail at rear. 4 swivel wheels Ø 125 mm with polyamide cover, 2 with brakes. Annular wheel guards. Capacity: 8 baskets 500 \times 500 mm per level, i.e. a total of 24 baskets.



Description	Overall Dim. I × W × h (mm)	Reference	Price
Trolley with 8 tiers (for horizontal storage of dishwasher baskets)	630 × 630 × 1785	804 193	
Trolley (for storage of dishwasher baskets on end)	1000 × 500 × 1785	804 196	
Polyamide cover with zip for trolley 8 tiers	585 × 600 × 1620	221 231	











- Openwork, sloped base to facilitate draining of cleaning water.
- Adjustable safety separation grids to fit the type of dishes used.
- On the trolleys with fold-away grids, the front grid can be hooked on to the rear for easy access when loading and unloading.









PLATE TROLLEYS

Stainless steel construction. Arched handles in tube 25 \times 25 mm with adjustable separations. 4 swivel wheels Ø 125 mm with polyamide cover including 2 brakes. Annular bumpers. Plates up to Ø 290 mm maximum.

Welded trolleys

Description	Overall Dim. I × W × h (mm)	With secure stacking partitions		+ remova	ation grills able front ill
		Ref.	Price	Ref.	Price
Trolley 200 plates	1065 × 450 × 810	800 541		800 542	
Trolley 300 plates	1065 × 450 × 1000	800 546		800 547	
Trolley 400 plates	1065 × 740 × 810	800 551		800 552	

Plate trolleys - delivered as flat pack item

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Trolley 200 plates with secure stacking partition	1065 × 450 × 810	800 561	
Trolley 300 plates with secure stacking partition	1065 × 450 × 1000	800 566	

Welded trolleys with raised platform

Raised platform, for a more ergonomic use: height 460 mm for trolley 200 plates and 485 mm for trolley 400 plates.

Description	Overall Dim. I × W × h (mm)	With secure stacking partitions				grills + r	paration emovable t grill
		Ref.	Price	Ref.	Price		
Trolley 200 plates	1065 × 450 × 1000	800 575		800 578			
Trolley 400 plates	1065 × 740 × 1000	800 576		800 579			

2 tier welded trolleys

Trolleys with 2 tiers allowing more storage and more confortable use. Welded construction, slightly sloping platforms for a good stability of stored products.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
2 tier trolley (shelf heights 350 & 785 mm)	930 × 670 × 1160	800 585	
2 tier trolley (shelf heights 600 & 1000 mm)	930 × 670 × 1410	800 586	

3 tier welded trolleys

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
3 tier trolley (shelf heights 290 & 690 and 1090 mm)	990 × 670 × 1410	800 587	

















Cutlery dispenser (capacity 5 pans GN 1/3, containers not provided), height 300 mm.

Plate trolley options

Description	Reference	Price
Optional cutlery dispenser (1)	800 571	
Optional divider for trolley 200 plates	228 263	
Optional divider for trolley 300 plates	228 264	
Optional divider for trolley 400 plates	228 265	
Polyamide cover for trolley 200 plates	228 196	
Polyamide cover for trolley 300 plates	228 197	
Polyamide cover for trolley 400 plates and 2 tier trolley height 1160 mm (2)	228 198	
Polyamide cover for trolley 200 plates with cutlery dispenser	229 600	
Polyamide cover for trolley 300 plates with cutlery dispenser	229 601	
Polyamide cover for trolley 400 plates with cutlery dispenser (2)	229 602	

- (1) Suitable for all plate trolleys except 2 tier trolleys (2) Dimension of the cover 1035 \times 700 \times height 920 mm

Option

Extra cost for plate trolleys with stainless steel wheels (83 instead of 80)





TROLLEYS FOR GN PANS

For draining and storage of GN pans, grids and covers. Stainless steel construction. Welded stainless steel tube. Tube 25 \times 25 mm. Removable grids in wired stainless steel Ø 6 and 4 mm. Removable stop bars. 4 swivel wheels Ø 125 mm with polyamide cover including 2 brakes. Annular bumpers. The trolleys have 4 tiers 325 mm high. Removable of second tier makes it possible to store up to 530 mm high.

Description	Overall Dim. I × W × h (mm)	Reference	Price
Storage trolley small model, 38 cases per tier	1270 × 620 × 1705	805 602	
Storage trolley large model, 51 cases per tier	1670 × 620 × 1705	<u>805 605</u>	
Cover for trolley, small model	1270 × 620 × 1705	229 517	
Cover for trolley, large model	1670 × 620 × 1705	229 518	

Option

Extra cost for trolleys for GN pans (small and large model) with stainless steel wheels (83 instead of 80)









RACK AND TRAY DOLLEYS



General purpose rack dolleys

Stainless steel construction. Base thickness 1,2 mm. Internal base dimensions: 510×510 mm. Bolted handle. 4 swivel wheels \varnothing 100 mm with galvanized steel cover. Max load: 80 kg.

Description	Overall Dim. I × W × h (mm)	Reference	Price
General purpose stainless steel rack dolley	515 × 515 × 165	800 101	
General purpose stainless steel rack dolley with handle	600 × 515 × 850	800 102	



Rack dolleys with ABS base

Stainless steel construction. Tube 25 \times 25 mm. Removable ABS tray. Internal base dimensions: 510 \times 510 mm. Bolted handle. 4 swivel wheels Ø 125 m with polyamide cover (includes 2 brakes). Annular bumpers. Max load: 150 kg.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Rack dolleys with ABS base	570 × 570 × 225	800 111	
Rack dolleys with ABS base and upstand	630 × 570 × 900	800 112	



Stainless steel rack and tray dolleys

Stainless steel frame construction 25 \times 25 mm. Removable stainless steel base 1,2 mm thick. Internal base dimensions: 510 \times 510 mm (rack dolley) and 750 \times 510 mm (largest tray dolley). Bolted handle. 4 swivel wheels Ø 125 m with polyamide cover including 2 brakes. Annular bumpers. Max load: 150 kg.

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Stainless steel rack dolley	570 × 570 × 225	800 125	
Stainless steel rack dolley with upstand	630 × 570 × 900	800 126	
Stainless steel tray dolley with upstand	870 × 570 × 900	800 130	



Accessories

Description	Reference	Price
Polyamide cover for rack dolleys 530 \times 530 \times h. 300 mm	230 532	
Polyamide cover 750 \times 510 \times h. 300 mm for trays dolleys	221 234	

Option

Extra cost for rack dolleys and tray dolleys* for GN pans (small and large model) with stainless steel wheels (83 instead of 80)

^{*} not suitable for rack dolley ref: 800 101 and 800 102)















Euronorm castor base

For trays or containers 600 \times 400 mm. Food quality stainless steel construction. Tray thickness 1.2 mm. Useful dimensions 610 \times 410 mm. Bolted handle. 4 swivel wheels Ø 100 mm with galvanized steel cover. Max load: 80 kg.

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Euronorm castor base	615 × 415 × 165	<u>800 105</u>	
Euronorm castor base with upstand	700 × 415 × 850	<u>800 106</u>	



SINKS ON WHEELS

Soaking sinks:

Height: 900 mm on wheels for soaking and washing large-sized baskets and kitchen utensils. Stainless steel construction, tank $600 \times 600 \times 300$ mm with drain plug, quarter-turn tap and stainless steel discharge tube, (42mm diameter) - 110 mm above finished floor level. Tubular frame 25 \times 25 mm with 4 spacers, 4 swivel wheels with polyamide cover, 2 with brakes.

Stainless steel sinks 140 litres:

- **Ref: 806 050:** with strainer grill and overflow plug. 4 swivel wheels Ø 125 mm, including 2 brakes with galvanized steel cover.
- Ref: 806 051: with draining plug + stop grill. 4 swivel wheels Ø 125 mm with polyamide cover including 2 brakes.

Polyethylene container with draining plug:

4 wheels with stainless steel cover: 2 fixed, 2 swivel \varnothing 160 mm.



Description	Overall Dim. I × W × h (mm)	Reference	Price
Stainless steel soaking sink 100 litres	740 × 740 × 900	806 066	
Stainless steel sink 140 litres	810 × 560 × 540	806 050	
Stainless steel sink 140 litres (raised height)	810 × 560 × 750	806 051	
Polyethylene sink 220 litres	900 × 700 × 735	816 155	
Polyethylene sink 310 litres	1200 × 800 × 805	<u>816 157</u>	
Polyethylene sink 500 litres	1200 × 800 × 1095	816 158	

Extra-cost for stainless steel wheels for sinks 806 050 - Ref.: 702 202















GASTRONORM CONTAINER STORAGE TROLLEYS



Strength:

max load 250 kg per trolley and 20 kg per level

Ergonimical:

longitudinal reinforcement bar on 10-17-20 tier trolleys and GN 2/1 trolley with 15 tier which allow a maximum accessibility for frontloading



804 212

804 237

Stainless steel construction. Square tubes 25 \times 25 mm. Welded tray runners with container stop. 4 swivel wheels Ø 125 mm, including 2 brakes, with polyamide cover. Annular bumpers. Overall dimensions: trolleys GN 1/1 size - 445 \times 655 mm, trolleys GN 2/1 - 660 \times 775 mm. Trolleys with 6 and 8 tiers include a top shelf. Max load: 20 Kg per tier and 250 Kg per trolley.

Welded tray runner GN trolleys



Description	e* (mm)	Height (mm)	Number of tiers	Reference	Price
GN 1/1 trolley with top shelf	81	760	6	804 201	
GN 1/1 trolley with top shelf	81	900	8	804 203	
GN 1/1 trolley	144	1650	10	804 204	
GN 1/1trolley	81	1490	15	804 206	
GN 1/1 trolley	81	1650	17	804 207	
GN 1/1 trolley	77	1785	20	804 209	
GN 2/1 trolley with top shelf	81	760	6	804 231	
GN 2/1 trolley with top shelf	81	900	8	804 233	
GN 2/1 trolley	144	1650	10	804 234	
GN 2/1trolley	81	1490	15	804 236	
GN 2/1 trolley	81	1650	17	804 237	
GN 2/1 trolley	77	1785	20	804 239	

(*) e: vertical space between tray runners.

Option

Extra-cost for GN trolleys, GN trolley (flat packed) and stackable trolley with 4 stainless steel wheels including 2 brakes (83 instead of 80)

Extra-cost for GN trolleys, GN trolley (flat packed) and stackable trolley with tie bars (84 instead of 80)

Transport trolley

Stainless steel construction. Square tubular uprights 25 \times 25 mm. Welded tray runners with stop blocks at the end. Closing bar for intensive use: transport inside a vehicle, loading, unloading, passing through doors whilst heavily loaded. Wheels Ø 125 with non protruding stainless steel cover to take up as little place as possible. Overall dimensions: 384 \times 583 mm, height 1485 mm. Space between sliders 81 mm.

Description	Reference	Price
Transport trolley GN 1/1 with 15 tiers	804 212	

















GN trolleys delivered flat packed

Delivered flat packed with shrink film delivery. Assembly by screw.

Description	e*(mm)	Height (mm)	Number of tiers	Reference	Price
GN 1/1 trolley (flat packed)	81	1490	15	804 216	
GN 1/1 trolley (flat packed)	81	1650	17	804 217	
GN 1/1trolley (flat packed)	77	1785	20	804 219	
GN 2/1 trolley (flat packed)	81	1490	15	804 246	
GN 2/1 trolley (flat packed)	81	1650	17	804 247	
GN 2/1 trolley (flat packed)	77	1785	20	804 249	

(*) e: vertical space between tray runners



GN stackable tray runner trolleys

Description	e* (mm)	Overall Dim. W × I × h (mm)	Number of tiers	Reference	Price
GN 1/1 stackable trolley	77	455 × 655 × 1785	20	804 229	
GN 2/1 stackable trolley	77	655 × 775 × 1785	20	804 259	

(*) e: vertical space between tray runners

Washable covers

Covers for 6-8 tier trolleys. Covers with zip for 10 tiers trolley GN and more.

Description	$W \times I \times h \text{ (mm)}$	For trolleys	Reference	Price
Cover	405 × 590 × 740	GN 1/1 with 6-8 tiers	221 235	
Cover	610 × 710 × 740	GN 2/1 with 6-8 tiers	<u>221 236</u>	
Cover	405 × 605 × 1325	GN 1/1 with 15 tiers *	221 240	
Cover	610 × 725 × 1325	GN 2/1 with 15 tiers	221 241	
Cover	405 × 590 × 1620	GN 1/1 with 10-17-20 tiers	228 168	
Cover	610 × 710 × 1620	GN 2/1 with 10-17-20 tiers	228 169	

(*) including transport trolley



Disposable cover (box)

Disposable covers in polyethylene thickness 50 microns: delivered by box of 100 covers

Description	For trolleys	Reference	Price
100 polyethylene cover	GN 1/1	228 170	
100 polyethylene cover	GN 2/1	228 171	



228 169

Unwinder for rolls of covers (rollers)

Stainless steel unwinder. Suits for rollers maxi length 80 cm and maxi diameter 30 cm.

Disposable covers in polyethylene, thickness 15 microns, delivered in roller of 180 pre-cut covers suitable for trolleys up to 1785 mm height.

Description	Dimensions (mm)	Reference	Price
Unwinder for rolls of covers	L 900 × W 430 × H. 300	805 776	
Roller of 180 covers GN 1/1	L 550 × Ø 260	221 440	
Roller of 180 covers GN 1/1	L 670 × Ø 260	221 439	









EURONORM RACKING TROLLEYS

Stainless steel 25 \times 25 frame construction. Argon welded tray runners with tray runner stops at each end. 4 swivel wheels Ø 125 mm, with polyamide cover (2 braked). Annular bumpers. The 9 tier trolleys include an upper shelf. Max load: 20 Kg per tier and 250 Kg per trolley.



Euronorm trolleys	Opening (mm)	e* (mm)	Overall Dim. $W \times I \times h$ (mm)	Number of tiers	Reference	Price
400 × 600 mm	400	70	540 × 725 × 900	9	804 155	
400 × 600 mm	400	125	540 × 725 × 1785	12	804 156	
400 × 600 mm	400	94	540 × 725 × 1785	16	804 157	
600 × 400 mm (1)	600	94	732 × 525 × 1785	16	804 158	
400 × 600 mm	400	75	540 × 725 × 1785	20	804 159	
600 × 400 mm (1)	600	75	732 × 525 × 1785	20	804 160	
400 × 800 mm	400	75	540 × 925 × 1785	20	804 161	
600 × 800 mm (1)	600	94	732 × 925 × 1785	16	804 162	
600 × 800 mm (1)	600	75	732 × 925 × 1785	20	804 163	

- (*) e: vertical space between tray runners.
- (1) 600 mm opening trolleys do not accept ABS trays.

THE TOURNUS ASSET

- Hygiene certified
- Sturdy trolleys
- Stainless steel wheels
- Rolling quality

Extra-cost for euronorm trolleys

Description	Reference	Price
Washable polyamide cover (for trolleys 400 \times 600 mm, with 400 opening - except 9 tier model).	229 519	

Option

Extra-cost for Euronorm trolley with 4 stainless steel wheels including 2 brakes (83 instead of 80)

Extra-cost for Euronorm trolley with tie bars (84 instead of 80)

STORAGE TROLLEYS

Stainless steel 25 \times 25 frame construction. Argon welded tray runners with runner stops at each end. 4 swivel wheels Ø 125 mm, with galvanized steel wheel cover, non protruding, designed for heavy loads, freezing environment (-40°C) and proving chambers.

Chambers.						
Euronorm storage trolleys	Opening (mm)	e* (mm)	Overall Dim. $W \times I \times h \text{ (mm)}$	Number of tiers	Reference	Price
600 × 800 mm	600	75	662 × 855 × 1775	20	814 321	
$800 \times 600 \text{ mm}$	800	75	862 × 655 × 1775	20	814 322	
1000 × 700 mm	1000	75	1062 × 755 × 1775	20	814 323	
1000 × 800 mm	1000	75	1062 × 855 × 1775	20	814 324	
With removabl	e shelf					
600 × 800 mm	600	75	662 × 855 × 1775	20	824 321	
800 × 600 mm	800	75	862 × 655 × 1775	20	824 322	
1000 × 700 mm	1000	75	1062 × 755 × 1775	20	824 323	
1000 × 800 mm	1000	75	1062 × 855 × 1775	20	824 324	













TROLLEYS FOR DOUGH CONTAINERS



Trolleys for round and rectangular dough containers. Welded stainless steel construction. Maximum load per level: 25 kg. Weight: 13 kg.

- Tube structure: uprights and spacers made of 25 × 25 mm section stainless steel tube, thickness 1,2 mm. 2 lower spacers made of 25 × 25 mm section stainless steel tube, thickness 1,2 mm.
- Slide bars: 7 levels of sliders made of stainless steel bent tube, Ø 12 mm, with spacing of 183 mm. Fitted into uprights and continuous argon welds with no added metal.
- Wheels: 4 swivel wheels Ø 125 mm with polyamide cover, 2 with brake.

Trolley for containers	Opening (mm)	Overall Dim. $W \times I \times h \text{ (mm)}$	Reference	Price
8 tier	195	470 × 660 × 1810	804 165	



FLOUR CONTAINERS

Stainless steel construction. 4 swivel wheels Ø 100 mm with galvanized steel cover.

Description	Overall Dim. W \times I \times h (mm)	Reference	Price
120 litre flour container + stainless steel lid	605 × 395 × 725	907 005	
120 litre flour container with dividing panel + s/ steel lid	605 × 395 × 725	806 150	



TROLLEYS FOR UTENSILS

- Hook trolley: Stainless steel construction. 4 swivel wheels Ø 100 mm with galvanized steel cover. 12 bars for utensils.
- Accessories holder trolley: Stainless steel construction. 4 swivel wheels Ø 100 mm with galvanized steel cover. 1 container GN 1/1, depth 40 mm removable, 3 bars for ustensils with 1hook.
- Chef's trolley: Stainless steel construction. 4 swivel wheels Ø 125 mm with polyamide cover, stainless steel axle and ball bearings. Sliding frame 7 GN 2/1 levels, 1 polyethylene worktop, 1 support for 6 poly. GN 1/6 depth 100 mm, pans provided, 1 lateral box for knives, 1 bar for accessories.

Description	Overall Dim. $W \times I \times h \text{ (mm)}$	Reference	Price
Hook trolley	660 × 640 × 1755	906 440	
Holder trolley	560 × 365 × 1600	801 310	
Chef's trolley	590 × 690 × 1750	801 331	









PLATE STACKING TROLLEYS

Stainless steel structure. Anodised aluminium tubes 25 \times 25 mm coating. Non-slip coating. Vertical space between tiers: 70 mm. Support adjustable to fit plate sizes (up to Ø 32 cm). The trolleys include 4 swivel wheels Ø 125 mm including 2 brakes, with polyamide cover.



Wall plate stacking trolleys

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Wall plate stacking, 1 stack: 10 plates	371 × 248 × 770	801 231	
Wall plate stacking, 2 stacks: 20 plates	711 × 248 × 770	801 232	

Plate stacking trolleys

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Plate stacking trolley, 2 stacks: 30 plates	420 × 670 × 1412	801 261	
Plate stacking trolley, 4 stacks: 60 plates	730 × 670 × 1412	801 262	
Plate stacking trolley, 4 stacks: 80 plates	730 × 670 × 1762	801 263	
Plate stacking trolley, 6 stacks: 120 plates	1040 × 670 × 1762	801 264	





- Excellent holding of plates: the plates rest on 4 points, are held on top and underneath thereby ensuring they are fully horizontal.
- Safe transport of plates thanks to the non-slip coating of the fingers and the patented clip system.

Covers for plate stacking trolleys

Covers with 2 vertical and horizontal zippers for handle.

Description	Reference	Price
Washable cover for trolley: 80 plates	228 176	
Washable cover for trolley: 120 plates	228 177	
Isotherm cover for trolley: 80 plates	228 179	
Isotherm cover for trolley: 120 plates	228 180	

















TROLLEYS FOR GN PANS



Welded stainless steel construction. Capacity: $2 \times GN$ 1/1 pans or $1 \times GN$ 2/1 pan, depth 200 mm (GN pans not provided). 4 swivel wheels Ø 125 mm, with polyamide cover, including 2 braked.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Stackable trolley for GN pans	740 × 625 × 850	806 071	

Extra cost for 4 stainless steel wheels - Ref: 702 180

BREAKFAST TROLLEY

Trolley with upper shelf and anti-fall gallery rails. 2×7 level 1/1GN tiers with 325 mm openings. With handle.4 swivel wheels with polyamide cover including 2 brakes. Annular bumpers.



Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Breakfast trolley	850 × 640 × 1020	800 066	



BAIN-MARIE HEATED TROLLEY

Stainless steel construction for GN 1/1 containers up to 200 mm deep (not supplied). Independant well regulated by separated thermostats with illuminated indicator. Heating by shielded resistances. Protection bumpers and lower shelf. Drain with 1/4 turn valve. 4 swivel wheels Ø 125 mm with polyamide cover including 2 brakes. Voltage 230V 50 Hz.



Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Bain-marie trolley, 2 containers	900 × 650 × 900	812 321	
Bain-marie trolley, 3 containers	1300 × 650 × 900	812 322	









KITCHEN TROLLEYS



- Bread trolley: Stainless steel construction. 4 swivel wheels Ø 125 mm, with polyamide cover, including 2 brakes. Rear preparation shelf for cutting bread. Width 350 mm, 2 copolyester 2/1 GN containers. Depth 200 mm on runners.
- Vacuum packed food trolley: Stainless steel construction. 4 swivel wheels Ø 125 mm, with polyamide cover, including 2 brakes. Removable waste bag folding holder 50 litres. Polyethylene sheet, perforated sheet. Polypropylene GN 1/1 container on slides
- Gutting trolley: Stainless steel construction. 4 swivel wheels Ø 125 mm, with polyamide cover. Perforated top. Polyethylene sliding drawer.
- Spice trolley: Stainless steel construction. 4 swivel wheels Ø 125 mm, with polyamide cover including 2 brakes. Provided with 8 copolyester containers GN 1/6 depth 100 + lids.



Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Bread trolley	770 × 700 × 775	801 341	
Vacuum packed food trolley	850 × 600 × 850	906 521	
Gutting trolley	850 × 600 × 850	906 520	
Spice trolley	720 × 410 × 750	906 446	

CLEARING TROLLEY



Delivered with 3 stainless steel 1/3 GN cutlery pans, 100 mm deep, waste chute with rubber flange. 4 swivel wheels with polyamide cover including 2 brakes. Annular bumpers.

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Clearing trolley	1330 × 640 × 920	800 061	

MULTI-PURPOSE TROLLEY



Trolley with 2 trays 1000 \times 600 mm. **Smooth and sturdy trays**. Horizontal handle. **Max load: 100 kg/ tray.** 4 swivel wheels Ø 125 mm including 2 brakes.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Multi-purpose trolley	1070 × 670 × 850	801 625	

Option

Extra cost for multi-purpose trolleys with stainless steel wheels (83 instead of 80)











PLATFORM TROLLEYS



Platform 1000×600 mm. 4 wheels: 4 swivel wheels Ø 160 mm, with galvanized steel cover, nylon tread. Max load: 350 Kg.

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Open aluminium platform trolley	1250 × 600 × 1000	802160	
Aluminium platform trolley with solid base	1250 × 600 × 1000	802 162	
Open S/ steel platform trolley	1200 × 600 × 1000	802 165	
S/ steel platform trolley with solid base	1200 × 600 × 1000	802 166	

Extra-cost for rubber bumpers on 3 sides - Ref. 702 211

Option

Extra cost for platform trolleys with stainless steel wheels \emptyset 160 mm (83 instead of 80)

LABORATORY TROLLEYS



Stainless steel tube 35 \times 35 mm. Removable stainless steel punnet basket. 4 swivel wheels Ø 125 mm with galvanized steel cover including 2 brakes

Description	Overall Dim. $I \times W \times h \text{ (mm)}$	Reference	Price
Single tray holder, basket 1220 \times 400 \times 500 mm	1310 × 500 × 750	801 271	
Double tray holder, basket 1220 \times 400 \times 500 mm	1310 × 500 × 1110	801 276	

MEAT HOOK TROLLEYS



Aluminium construction. Max load: 600 kg. 4 wheels: 2 fixed, 2 swivel, with galvanized steel cover Ø 160 mm (small trolley model), Ø 200 mm (large trolley model).

Description	Overall Dim. $I \times W \times h$ (mm)	Reference	Price
Meat hook trolleys small model	1150 × 750 × 1800	802 010	
Meat hook trolleys large model	1800 × 750 × 1800	802 020	

- Extra-cost for trolley equipped with 4 stainless steel wheels Ø 160 mm : 702 201
- Extra-cost for trolley equipped with 4 stainless steel wheels Ø 200 mm : 702 203

ANGLE BAR



Description	Lengths (mm)	Reference	Price
Angle bar	1500	803 392	
Angle bar	2000	803 393	
Angle bar	2500	803 394	

