

MODEL NO: 2024203

For boiling, steaming, frying, braising, simmering as well as pressureless cooking and pressure cooking for shorter cooking times. For cooking meat, quick-fried meat, egg products, fish, milk products and side dishes.

## **Product Advantages:**

- Housing made completely of stainless steel.
- · Visible surfaces with polished and satin
- finish, 320 grit.
- · Buckling resistant, self-supporting, closed
- · construction with side walls, rear wall and
- bottom.
- Tightly welded top plate with lateral drain
- · channels for easy cleaning.
- Pressure reduction system OptimaExpress.
- Fast pressure release system OpenExpress.
- Core temperature sensor as standard.
- ERGO CONTROL operating concept.

## <u>Installation requirements:</u>

• Electrical supply provided by customer.





Technical Data:	
Width x Height x Depth (mm)	1600 x 700 x 850
Effective area	1
Dim.: effect. Area (mm)	1020 x 210 x 540
Nominal capacity (L):	116
Nominal fill quantity (L):	94
Connected load (elect.) (kW):	19.2
Voltage (V) / EC:	415 3 phase AC
Recommended fuses (A):	3 x 32
Frequency range (Hz):	50
Standard gas pressure (mbar)	20
Natural gas	
Standard gas pressure (mbar)	30 (DE), 50 (EU)
Liquid gas	
Net weight (kg):	330
Gross weight (kg):	370
Heat emission latent (W):	7680
Heat emission sensitive (W):	8640
Type of protection:	IPX5









