



For all-purpose cooking in liquid in commercial kitchens, for vegetables, starch side dishes, soups, sauces, in particular also acidic dishes as well as desserts.

Product Advantages:

- Housing made completely of chrome nickel steel (1.4301) / (304).
- Tightly welded top plate with lateral drain channels for easy cleaning.
- Double-jacketed kettle with separate VAPRO steam generator for low energy and water consumption and high efficiency.
- Short heating up times with VAPRO rapid steam system.
- 3 cooking programmes as standard (light simmering, medium boiling and strong boiling).
- Constant operational readiness due to the steam generator with process water monitoring Double walled hinged lid with spring loaded swivel joints as standard.
- Ideal kettle positioning prevents spills and guarantees that the kettle is fully emptied even into high containers.
- Equipped for connection to a power optimization system.

Installation requirements:

- Electrical supply provided by customer.



Technical Data:

Width x Height x Depth (mm):	1300 x 700 x 850
Effective area:	1
Dim.: effect. Area (mm):	XXX x 645 x XXX
Diameter (mm):	665
Nominal capacity (L):	200
Connected load (elect.) (kW):	26.2
Voltage (V) / EC:	415 3 phase AC
Recommended fuses (A):	3 x 50
Frequency range (Hz):	50
Standard gas pressure (mbar) Natural gas	20
Standard gas pressure (mbar) Liquid gas	30 (DE), 50 (EU)
Heat-up time (Min.):	42
Net weight (kg):	285
Gross weight (kg):	320
Heat emission latent (W):	5200
Heat emission sensitive (W):	910
Type of protection:	IPX5

