







A team player for professional kitchens:

Two parallel operating cooking modes in one combi steamer

Flexibility

Cooking processes in the upper and lower chambers are **completely independent** of one another.



Individuality/Capacity

More capacity in the same space; better adapted to daily requirements (compared to floor-mounted appliances).



Hygiene

The closed housing caters for **easy cleaning**.

■ MagicPilot

An operating concept as easy to use as your smartphone.



Automatic cleaning system. Economical water consumption.



Energy efficiency

Hygienic cooking chamber doors with sealed triple glazing, heat exchanger and lower connected loads.







Best heavy equipment innovation



Capacity concept

Hygier Seamle surface easy to

FlexiCombi team



Installation

Separate cooking chambers with separate connections.

Appliance is already fully assembled on delivery.

- Lowest drain connection point at a height of 180 mm (no installation through the floor).
- Workplace safety
 Highest insertion level is under 1600 mm*.
 - * For 6.x appliance on top of 6.x appliance
- Required space GN 1/1 and GN 2/1 appliances can also be combined without any change to the appliance dimensions.
- Connectivity

WLAN[™] as standard feature now

** in all certified countrie

Optimum utilization of cooking chamber with consistently low connected loads. With the FlexiRack® special dimensions you can produce up to 50 % more* cooked food when roasting and baking.





Technical data



					team		
Model versions	FlexiCombi [®] 6.1 FlexiCombi [®] 6.1	FlexiCombi [®] 6.1/6.2 FlexiCombi [®] 6.2/6.1	FlexiCombi [®] 6.2 FlexiCombi [®] 6.2	FlexiCombi® 6.1 / 10.1 FlexiCombi® 10.1 / 6.1	FlexiCombi [®] 6.2 / 10.1 FlexiCombi [®] 10.1 / 6.2	FlexiCombi® 6.1 / 10.2 FlexiCombi® 10.2 / 6.1	FlexiCombi® 6.2/10.2 FlexiCombi® 10.2/6.2
MKN Model No.	DKECOD615-615G2	DKECOD621-615G2 / DKECOD615-621G2	DKECOD621-621G2	DKECOD115-615G2 / DKECOD615-115G2	DKECOD115-621G2 / DKECOD621-115G2	DKECOD121-615G2 / DKECOD615-121G2	DKECOD121-621G2 / DKECOD621-121G2
Appliance dimensions (W x D x H)	997 x 874 x 1700	997 x 874 x 1700	997 x 874 x 1700	997 x 874 x 1900	997 x 874 x 1900	997 x 874 x 1900	997 x 874 x 1900
Connected load (electrical)	2x 10.4 kW	10.4 and 20.9 kW	2x 20.9 kW	10.4 and 15.9 kW	20.9 and 15.9 kW	10.4 and 30.5 kW	20.9 and 30.5 kW
Capacities	6.1 – 6.1	6.1 – 6.2	6.2 – 6.2	6.1 – 10.1	6.2 – 10.1	6.1 – 10.2	6.2 – 10.2
FlexiRack® (530 x 570 mm)	2 x 6 (12)	2 x 6 (12)	2 x 6 (12)	6 and 10 (16)	6 and 10 (16)	6 and 10 (16)	6 and 10 (16)
GN 1/1 (530 x 325 mm)	2 x 6 (12)	6 and 12 (18)	2 x 12 (24)	6 and 10 (16)	12 and 10 (22)	6 and 20 (26)	12 and 20 (32)
GN 2/1 (530 x 650 mm)	-	1 x 6	2 x 6 (12)	-	1 x 6	1 x 10	6 and 10 (16)
Baking size (600 x 400 mm)	2 x 5 (10)	2 x 5 (10)	2 x 5 (10)	5 and 8 (13)	5 and 8 (13)	5 and 8 (13)	5 and 8 (13)
Plates Ø 28 mm on FlexiRack® grids	2 x 24 (48)	2 x 24 (48)	2 x 24 (48)	24 and 40	24 and 40	24 and 40	24 and 40
12 Chickens (1300 g) on FlexiRack ® chicken grill rack instead of 8 chickens on GN 1/1	2 x 24 (48) instead of 2 x 16 (32)	24 and 32 (56) instead of 16 and 32 (48)	2 x 32 (64)	24 and 36 (60) instead of 16 and 24 (40)	32 and 36 (68) instead of 32 and 24 (56)	24 and 48 (72) instead of 16 and 48 (64)	32 and 48 (80)
4 Geese (5 kg each) on FlexiRack ® roasting tray instead of 2 geese on GN 1/1	2 x 12 (24) instead of 2 x 6 (12)	2 x 12 (24)	2 x 12 (24)	12 and 20 (32) instead of 6 and 10 (16)	12 and 20 (32)	12 and 20	12 and 20
8 Rump steaks (220 g each) on GN 1/1 grill grid	2 x 48 (96)	48 and 96 (144)	2 x 96 (192)	48 and 80 (128)	96 and 80 (176)	48 and 160 (208)	96 and 160 (256)
8 Salmon steaks (180 g each) on GN 1/1 grill grid	2 x 48 (96)	48 and 96 (144)	2 x 96 (192)	48 and 80 (128)	96 and 80 (176)	48 and 160 (208)	96 and 160 (256)
12 Chicken breasts (140 g each) on GN 1/1 grill grid	2 x 72 (144)	72 and 144 (216)	2 x 144 (288)	72 and 120 (192)	144 and 120 (264)	72 and 240 (312)	144 and 240 (384)
4 Roast pork joints (4 kg) on FlexiRack ® roasting tray instead of 2 joints on GN 1/1	2 x 12 (24) instead of 2 x 6 (12)	2 x 12 (24)	2 x 12 (24)	12 and 20 (32) instead of 6 and 10 (16)	12 and 20 (32)	12 and 20	12 and 20
3 Roast beef joints (4 kg) on FlexiRack [®] roasting tray instead of 2 joints on GN 1/1	2 x 9 (18) instead of 2 x 6 (12)	9 and 12 (21) instead of 6 and 12 (18)	2 x 12 (24)	9 and 15 (24) instead of 6 and 10 (16)	12 and 15 (27) instead of 12 and 10 (22)	9 and 20 (29) instead of 6 and 20 (26)	12 and 20 (32)
16 Croissants (90 g each) on FlexiRack® baking tray instead of 8 croissants on GN 1/1	2 x 96 (192) instead of 2 x 48 (96)	2 x 96 (192)	2 x 96 (192)	96 and 160 (256) instead of 48 and 80 (128)	96 and 160 (256) instead of 96 and 80 (176)	96 and 160 (256) instead of 48 and 160 (208)	96 and 160 (256)
12 Pretzels (100 g each) on FlexiRack® baking tray instead of 8 pretzels on GN 1/1	2 x 72 (144) instead of 2 x 48 (96)	72 and 96 (168) instead of 48 and 96 (144)	2 x 96 (192)	72 and 120 (192) instead of 48 and 80 (128)	96 and 120 (216) instead of 96 and 80 (176)	72 and 160 (232) instead of 48 and 160 (208)	96 and 160 (256)
12 Schnitzels (escalopes, 180 g each) on FlexiRack® roasting tray instead of 8 schnitzels on GN 1/1	2 x 72 (144) instead of 2 x 48 (96)	72 and 96 (168) instead of 48 and 96 (144)	2 x 96 (192)	72 and 120 (192) instead of 48 and 80 (128)	96 and 120 (216) instead of 96 and 80 (176)	72 and 160 (232) instead of 48 and 160 (208)	96 and 160 (256)



Optional equipment and accessories:

- Smokelnside integrated smoking function for upper chamber
- Two-in-one cleaning cartridges
- Two position safety door lock
- Left hand hinged door GN lengthwise insertion
- FlexiRack® trays and grids
- GN containers, GN grids and baking & roasting trays
- Special voltage
- Interface for connection to an energy optimization system according to DIN 18875 and potential free contact
- ETHERNET interface
- MKN Grease Collection System

■ MagicPilot

WaveClean

GreenInside



FlexiRack



MKN Maschinenfabrik Kurt Neubauer GmbH & Co. KG Halberstaedter Strasse 2a 38300 Wolfenbuettel/Germany Phone +49 (0) 5331 89-0 Fax +49 (0) 5331 89-280



www.mkn.com