



world of cooking

The **FlexiChef**®

smart cooking. smart cleaning.



The FlexiChef® – Your all-rounder in the kitchen!




Cooking

Perfect for soups, stews or pasta. Optimised, gentle cooking processes ensure top food quality



Grilling/Shallow Frying

Perfect for preparing meat, fish or vegetables; even heat distribution



Deep frying

Fried food in premium quality



ReadyXpress® (Option)

High speed cooking in FlexiChef® accelerates kitchen processes significantly



FlexiZone®

Divide the pan in up to three zones using the FlexiZone® feature. Each zone can be individually controlled.



Sous vide cooking

Cooking in vacuum sealed plastic bags

Intelligent operating system – Fast. Large. Clearly arranged.

The MKN MagicPilot Intuitive operation and a perfect overview

- Faster hardware caters for a smoother workflow
- User friendly handling uniform control display for diverse MKN appliances

Guided Cooking – User navigation through the cooking process

- Automatic cooking processes
- Food quality can be reproduced fast and safely
- Useful notes as instructions; integration of photos possible
- Automatic control functions for perfect quality during cooking



Taking speed to the next level

approx. 150 min.***



approx. 96 min.**



approx. 52 min.*

The new **FlexiChef**

Up to **2 x** faster
than conventional pressure
cooking equipment***

Up to **3 x** faster
than conventional cooking**



up to
10%

faster than the
previous model

Production time with ReadyXpress®**** e.g. beef goulash

Up to 65% time savings

* compared to previous MKN technology ** compared to conventional MKN pressure cooking equipment *** compared to conventional MKN technology **** optional in FlexiChef®

SpaceClean® – The first and only fully automatic cleaning system for pans*



Easier to operate

Orbital cleaning head tightly integrated in the lid



Faster

Set-up procedure not required



Faster

amortisation

Up to **90%**** less water consumption
Only 26 l water per cleaning cycle

*Option ** when using SpaceClean® compared to manual cleaning of conventional cooking equipment



SmartBoiling – the new energy efficient boiling process

	standard cooking appliance	FlexiChef® (SmartBoiling)
Energy consumption	7 kWh	0.2 kWh
Costs per 30 ct/kWh	2.10 €	0.06 €
Evaporated water	13 litres	0 litres
CO ₂ emissions	2.9 kg	>0.1 kg

Discover the next generation of cooking with SmartBoiling. With impressive **energy savings of 99%** compared to conventional boiling, SmartBoiling sets new standards in your kitchen.

Energy consumption - SmartBoiling vs. conventional boiling process. Figures refer to a 20 minute boiling process for 75 litres water.

*compared to conventional boiling

Top quality for efficiency and a long lifespan

More sustainability

New ways of thinking. The MKN FlexiChef® paves the way for groundbreaking and sustainable practices in cooking. Uncompromising quality, innovative features and an impressive package of user benefits, with the chef always in focus.

GreenHighlights in the FlexiChef®

Innovation and sustainability combined in perfection

Easy Up & Down – New lifting system in FlexiChef®*



New lifting system in FlexiChef®*

Frying baskets can be lifted easily and safely out of the pan and set aside.

Benefits:

- Ergonomic design = safety for the user
- Easy and safe lifting of heavy/hot baskets
- 20% lighter baskets when fully loaded as by other systems
- Guaranteed success: perfectly cooked food due to automatic lifting of baskets at precisely the right time

* Optional accessories required



The future of digital commercial kitchens

WLAN*: Standard feature now



OPC UA interface

Connection to kitchen control system DIN 18898 (via OPC UA interface, open standard)



REST API interface

Connection with your own platforms and external platforms possible with Rest-API/Swagger interface



Software updates using cloud or app

* in all certified countries



FlexiZone®

Grilling/shallow frying, cooking or deep frying on up to three zones which can be operated separately. Energy is only used where required.



up to **66%***
energy savings

Turbo PowerBlock

- Optimal energy management due to extensive sensor technology in pan bottom
- Energy is supplied only where needed
- Excellent heat storage properties
- Works well together with energy optimisation systems
- Robust and durable, easy replacement of components



* Compared to working with the FlexiChef® without using the FlexiZone®

The MKN FlexiChef®

Product overview and technical data

FlexiChef®	Size 1 (50 l)	Size 2 (75 l)	Size 2 (100 l)	Size 3 (100 l)	Size 3 (150 l)
Dimensions					
Length: mm	1100	1300	1300	1600	1600
Carcass width: mm	850	850	850	850	850
Carcass height: mm	750	750	750	750	750
Connection module	Optional connection to MKN OPTIMA 850 possible, additional space not required				
Connections					
Electric 400 V					
Electric load MaxPower: kW	14.7	22.4	22.4	34.0	34.0
Electric load FlexPower: kW	13.1	17.2	17.2	26.2	26.2
For 380 - 415 V					
Fuse protection MaxPower: A	35	50	50	63	63
Fuse protection FlexPower: A	25	32	32	50	50
Mains / Frequency	3 (N)PE AC / 50 Hz or 60 Hz				
Residual current device (RCD)	Recommended fuse protection (provided by customer), type A, 300 mA				
Feed water / waste water					
Cold water (drinking water)	Volume flow min. 13 l/min, pressure 2-6 bar, water hardness: < 4.5 mmol/l, dimensions 3/4" AG, DN 20				
Warm water (drinking water max. 60°C)					
Waste water (drain water)	max 80°C, volume flow max 50l/min (fixed connection) or max. 70l/min (floor drain), DN 50				
Skillet pan					
Dimensions: mm	523 x 543 x 225	723 x 543 x 225	723 x 543 x 315	1023 x 543 x 225	1023 x 543 x 315
Nominal capacity: l	50	75	100	100	150
Max. oil capacity: l	25	35	35	49	49

Optional equipment

Hanging system for baskets	- Shelf	- Shelf unit between Team
- Frying basket	- Ladle (unperforated)	appliances
- Cooking basket	- Ladle (perforated)	- Transport trolley for GN
	- Spatula for draining	containers
Hanging system for GN	- Straining sieve	- Portable oil filtration system
containers	- Wiper	75 l (230 V)
- GN container (unperforated)	- Pan scraper	- Oil filter papers
- GN container (perforated)	- Cleaning brush	(50 pieces per box)
	- Barcode scanner	- Care & Protection

FlexiChef® Team	Sizes 1 + 1	Sizes 2 + 2	Sizes 3 + 3	Sizes 1 + 2	Sizes 1 + 3	Sizes 2 + 3
Dimensions						
Length: mm	2200	2600	3200	2400	2700	2900
Carcass width: mm	850	850	850	850	850	850
Carcass height: mm	750	750	750	750	750	750
Connection module	Optional connection to MKN OPTIMA 850 possible, additional space not required					
Connections						
Electric 400 V						
Electric load MaxPower: kW	14.7 + 14.7	22.4 + 22.4	34.0 + 34.0	14.7 + 22.4	14.7 + 34.0	22.4 + 34.0
Electric load FlexPower: kW	13.1 + 13.1	17.2 + 17.2	26.2 + 26.2	13.1 + 17.2	13.1 + 26.2	17.2 + 26.2
For 380 - 415 V						
Fuse protection MaxPower: A	35 + 35	50 + 50	63 + 63	35 + 50	35 + 63	50 + 63
Fuse protection FlexPower: A	25 + 25	32 + 32	50 + 50	25 + 32	25 + 50	32 + 50
Mains / Frequency	3 (N)PE AC / 50 Hz or 60 Hz					
Residual current device (RCD)	Recommended fuse protection (provided by customer), type A, 300 mA					
Feed water / waste water						
Cold water (drinking water)	Volume flow min. 13 l/min, pressure 2-6 bar, water hardness: < 4,5 mmol/l, dimensions 3/4" AG, DN 20					
Warm water (drinking water max. 60°C)						
Waste water (drain water)	max 80°C, volume flow max 50l/min (fixed connection) or max. 70l/min (floor drain), DN 50					
Skillet pan						
Dimensions: mm	See dimensions of the FlexiChef® single units!					
Nominal capacity: l	50 + 50	75 + 75	100 + 100	50 + 75	50 + 100	75 + 100
Max. oil capacity: l	25 + 25	35 + 35	49 + 49	25 + 35	25 + 49	35 + 49

Optional equipment

You can optimize your FlexiChef® with a comprehensive range of accessories suitable for every kitchen. These are all geared to meet your requirements, from ladles to transport trolleys. Our packs are the perfect solution for optimizing diverse applications in any professional kitchen.

Starter pack

- Spatula for draining
- Wiper
- Shelves
- Ladles (perforated and unperforated)

Cooking pack

- Hanging system for baskets
- One set of cooking baskets

GN-Pack

- Hanging system for GN containers
- Transport trolley for portioning incl. GN 1/1 container
- Straining sieve

Deep fat frying pack

- Hanging system for baskets
- One set of frying baskets