

# BOILING KETTLES

## With tilting hemispherical tanks

**200 to 500 litres** (other capacity please contact us).

**With or without scraper arm**

**For blanching, browning, cooking, cooling, ...**

For sauces, meat-based dishes, vegetables, pasta, desserts, speciality dishes, a wide range of mixtures,...

### Main points:

- Strength
- Accurate control
- Uniformity when cooking

CAPIC's boiling kettle with its hemispherical tank and double jacket allows fast, risk-free, uniform cooking.

The design of the kettle body and the supporting tubular frame facilitates cleaning and hygiene.

The body's eccentric axis of rotation allows complete emptying into a standard container 700 to 750 mm high (steady tilting action can be stopped in any position).

Heating: steam. Pressure from 2 to 6 bars. Alternative: steam generation by gas heating or separate electric generator.

Options: Drainage tap, water meter, scraper arm, cooling, temperature controls, traceability software.



| Capacity (L) | External dimensions (mm)  |       |        |                            |       |        | Dimensions of vat (mm) |     |
|--------------|---------------------------|-------|--------|----------------------------|-------|--------|------------------------|-----|
|              | with vertical scraper arm |       |        | with removable scraper arm |       |        | Ø      Height          |     |
|              | Length                    | Depth | Height | Length                     | Depth | Height |                        |     |
| 200          | 1660                      | 1440  | 1910   | 2100                       | 1440  | 2450   | 750                    | 625 |
| 300          | 1780                      | 1440  | 1980   | 2100                       | 1440  | 2450   | 880                    | 690 |
| 400          | 1850                      | 1530  | 2015   | 2100                       | 1530  | 2450   | 950                    | 775 |
| 500          | 1890                      | 1530  | 2110   | 2100                       | 1530  | 2450   | 1000                   | 850 |



Clamping device for the scraper arm and satellite.



Inclined, removable scraper arm and satellite mixer.



Vertical, reinforced scraper arm supported at bottom of tank..

