



Technical Data:	
Loading	15 GN 1/1 h. 65 mm
Space between Sliders	71 mm
External Dimensions	528 x 821 x 1750 mm
Internal Dimensions	330 x 590 x 1105 mm
External Volume	0.759 m ³
Internal Volume	0.215 m ³
Weight when empty	104 kg
Connected Load	240 1 Phase AC - 50 Hz
Power Input	230 W
Current	1.8 A
Power Consumption	0.23 kWh
Protection Index	25
Standards	NF EN 60335-1 NF EN 60335-2-49
Max. Loading	120 kg
Type of Refrigerent	R134A
Power Refrigerating	230 W

Product Description:

- Made of food quality stainless steel.
- Insulation of walls 45 mm rock wool + 20 mm melamine foam.
- Insulation of door 45 mm thick with rock wool. Inside entirely radiused, with press-drawn sliders and base.
- Door with removable seal opens 270°.
- Carrying handles on sides and back.
- Wheels Ø 125 mm with polyamide cover, 2 with brakes.
- Circumferential bumper.
- Fan-assisted refrigeration controlled by an electronic thermostat with digital readout and the following functions:
 1. Adjustment range of set value from 0 to 10 °C.
 2. Possibility of deferred start.
 3. Dysfunction alarms for cabinet and refrigerated unit maintenance.
- Spiral power cable 3G1.5 with moulded plug + plug support.

Options:

- Extra-cost for lock and key (Reference Number: 707961)



Front View

Side View

